

P1.5mm Foable LED Poster Technical Specifications

Item	Specification
Product Name	Indoor Foldable LED Poster Display
Pixel Pitch	P1.5mm
Cabinet Size	640 × 1920 × 35 mm
Display Size	640 × 1920 mm
Resolution	426 × 1280 Pixels
Pixel Density	444,444 Pixels/m ²
LED Package	GOB
LED Type	SMD1010
Brightness	800–1200 nits
Refresh Rate	≥3840Hz
Gray Scale	16 Bit

Contrast Ratio	6000:01:00
Viewing Angle	H160° / V160°
Color Temperature	3000K–10000K Adjustable
Frame Rate	50 / 60Hz
Input Voltage	AC100–240V, 50/60Hz
Average Power Consumption	≤180W
Maximum Power Consumption	≤550W
Operating Temperature	-10℃ ~ +40℃
Operating Humidity	10%–90% RH
Protection Level	Front IP40(Indoor)
Cabinet Material	Aluminum Alloy
Maintenance	Front Service
Control System	NovaStar TB10 Plus
Input Interfaces	HDMI / USB / WiFi / RJ45 Ethernet

Content Management	USB Plug & Play / WiFi / Cloud CMS (Optional)
Cascade Function	Multi-screen Synchronous Display
Installation	Mobile Floor Standing
Wheel Type	Heavy-duty Lockable Casters
Lifetime	≥100,000 Hours
Certification	CE / RoHS
Warranty	2 Years

